



NOTES:

CONNECTIONS	
A	COMPRESSED AIR OUTLET 2" MALE
B	ELECTRICAL ENTRY 58,5 mm
C	OIL TANK DRAIN 3/4" FEMALE WITH PLUG
D	AIR COOLING FLOW RATE 23 m3/min
E	CONDANSATE DRAIN POINT
F	WEIGHT 2420

NOTE:
IT IS RECOMMENDED THAT A MINIMUM OF 90 cm CLEARANCE ON ALL SIDES AND ABOVE THE COMPRESSOR FOR MAINTENANCE PURPOSES

A	ADD TABULATION, TANK DRAIN, ELEC,NOTE	Y.S.	LK.	P.O.	02 MAR 07
REV	DESCRIPTIONS	DRAW	CHKD	APPR.	DATE

THIS DRAWING IS THE PROPERTY OF ANAKA HANNA INC. AND IS TRANSMITTED IN CONFIDENCE. NEITHER RECEIPT NOR POSSESSION CONFER OR TRANSFERS ANY RIGHT TO REPRODUCE, USE OR DISCLOSE, IN WHOLE OR PART, DATA CONTAINED HEREIN FOR ANY PURPOSE, WITHOUT THE WRITTEN PERMISSION OF ANAKA HANNA INC.

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE IN INCHES		CONTRACT NUMBER		ERS 160 COMPRESSOR DIMENSIONS
FRACTIONS	DECIMALS	DATE OF DRAWING	11 JAN 2007	
± .XX ±	± .XX ±	DRAFTER/AN	CHECKER	CODE IDENT NO.
ANGLES ± .XX ±	ANGLES ± .XX ±	V. SAKAL	I. KARALAN	
± .XXX ±	± .XXX ±	ENGINEER	FUNCTION DESIGN	SIZE DRAWING NO. A0 00-1600-9000
		B. OZKAN		
NEXT ASSY USED ON APPLICATION		MANUFACTURING	WELDING	SIZE A0
		APPROVED	R. OKÇON	SCALE 1:10 UNIT MM LB SHEET OF

